

Apple Cinema Displays | Pocket Card



| | 20-inch Display | 23-inch Display | 30-inch Display |
|-----------------------------------|--|-----------------------|-----------------------|
| Model | M9177 | M9178 | M9179 |
| Screen type | Thin film transistor (TFT) active-matrix liquid crystal display (AMLCD) | | |
| Resolution¹ | 1680 x 1050 pixels | 1920 x 1200 pixels | 2560 x 1600 pixels |
| Display colors | 16.7 million (maximum) | | |
| Viewing angle² | 178° horizontal, 178° vertical | | |
| Brightness² | 250 cd/m ² | 270 cd/m ² | 400 cd/m ² |
| Contrast ratio² | 400:1 | | 700:1 |
| Response time² | 14 ms | | |
| Pixel pitch | 0.258 mm | | 0.250 mm |
| User controls³ | Display power, system sleep, system wake, brightness, and display tilt | | |
| Cables | DVI, FireWire 400, USB 2.0, and DC power (24.5 V) | | |
| Connectors | Two-port, self-powered USB 2.0 hub, two FireWire 400 ports, and Kensington security port | | |

¹Optimum; ²Typical; ³Hardware and software.



Apple Cinema Displays | Pocket Card



This table summarizes compatibility of displays with Mac desktop and portable systems.

| | 20-inch Display | 23-inch Display | 30-inch Display |
|--------------------|--|-----------------|-----------------|
| Mac mini | All Mac mini models | | N/A |
| iMac | All Intel-based iMac models ⁴ | | N/A |
| Power Mac | Any new dual- or quad-core Power Mac G5; support for two 30-inch displays requires two dual-link DVI ports | | |
| MacBook | All MacBook models ⁴ | | N/A |
| MacBook Pro | All MacBook Pro models | | |

⁴Requires Apple Mini-DVI to DVI Adapter.

Options include the iSight Accessory Kit, VESA Mount Adapter, Kensington Slim Kevlar MicroSaver Lock, and AppleCare Protection Plan.

For more information and technical specifications, visit www.apple.com/uk/displays/specs.html.

