



PRODUCTS | Multifunction Monochrome Laser



NEW!
LEXMARK X652DE MFP

Efficient monochrome MFP with the added benefit of fax!

[Get A Quote](#)
[FIND A DEALER](#)
[BUY ON LINE](#)
[Interactive tour](#)
[Support](#)
[Printer brochure](#)

OVERVIEW SUPPLIES AND OPTIONS TECH SPECS Q AND A

Print Technology	Laser, Monochrome
UNSPSC Code	43212110
Function	Colour Scanning Copying Faxing Network Scanning Printing .
Supplies: Functions only with replacement cartridges designed for use in Europe, the Middle East and Africa	
Print Speed (A4 mono): Up to	43 ppm
Print Speed (A4 mono) Duplex: Up to	29 spm
Print Speed (Letter mono): Up to	45 ppm
Print Speed (Letter mono) Duplex: Up to	30 spm
Time to First Page (Black) As fast as	8.0 seconds
Copy Speed (A4, Black): Up to	43 cpm
Time to First Copy (Black) As fast as	7.5 seconds
Simplex Scan Speed (A4 mono): Up to	55 sides per minute
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 600 x 600 dpi
Scanning Resolution	600 X 600 dpi (mono)
Processor	600 MHz
Memory, standard	256 MB
Memory network model, maximum	1280 MB
Expandable Memory Options	Yes
Apple Macintosh Operating Systems Supported	Apple Mac OS X Apple Mac OS 9.x
Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5 Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
Linux Operating Systems Supported	Linpus Linux Desktop 9.2, 9.3 Red Hat Enterprise Linux WS 3.0, 4.0, 5.0 SUSE Linux Enterprise Server 8.0, 9.0, 10.0 SUSE Linux Enterprise Desktop 10 openSUSE 10.2, 10.3, 11.0 Linspire Linux 6.0 Debian GNU/Linux 4.0

	Red Flag Linux Desktop 5.0, 6.0 Ubuntu 7.10 Ubuntu 8.04 LTS		
Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 Microsoft Windows XP Microsoft Windows Server 2003 Microsoft Windows XP x64 Microsoft Windows Server 2003 running Terminal Services Microsoft Windows 2000 Server running Terminal Services Microsoft Windows Server 2003 x64	Novell Operating Systems Supported	Microsoft Windows Server 2008 x64 running Terminal Services Novell® Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS) Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)
	Microsoft Windows Server 2003 x64 running Terminal Services Microsoft Windows Vista Microsoft Windows Vista x64 Microsoft Windows Server 2008 Microsoft Windows Server 2008 x64 Microsoft Windows Server 2008 running Terminal Services	UNIX Operating Systems Supported	Sun Solaris SPARC 8, 9, 10 Sun Solaris x86 10 HP-UX 11.11, 11.23, 11.31 IBM AIX 5.2, 5.3, 6.1
		Other Operating Systems Supported	IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP
		Paper Handling Standard	Integrated Duplex 100-Sheet Multipurpose Feeder 550-Sheet Input Tray 550-Sheet Output Bin
		Paper Handling Optional	400-Sheet Universally Adjustable Tray with Drawer 550-Sheet Drawer 250-Sheet Drawer Optional furniture required. 2,000-Sheet High-capacity Feeder
		Paper Input Capacity, Standard: Up to	650 pages at 80 gsm bond
		Paper Input Capacity, Maximum: Up to	3200 pages at 80 gsm bond
		Paper Output Capacity, Standard: Up to	550 pages at 80 gsm bond
		ADF Paper Input Capacity : Up to	75 pages at 80 gsm bond
		Envelope Capacity	10
		Finishing Option?	No
		Paper Output Capacity, Maximum: Up to	550 pages at 80 gsm bond
		Number of Paper Inputs, Standard	2
		Number of Paper Inputs, Maximum	6
		Media Types Supported	Card Stock Dual Web Labels Envelopes Integrated Labels Paper Labels Plain Paper Polyester Labels Transparencies Vinyl Labels Refer to the Card Stock & Label Guide
		Media Sizes Supported	10 Envelope 7 3/4 Envelope 9 Envelope A4 A5 DL Envelope Executive Folio JIS-B5 Legal Letter Statement Universal
		Supplies Yield	25,000*-page High Yield Print Cartridge *Average standard page yield value declared in accordance with ISO/IEC 19752 7,000*-page Print Cartridge
		Standard Ports	Fast Ethernet One Internal Card Slot USB 2.0 Specification Hi-Speed Certified (Type B) USB port (Type A) compatible with USB 2.0 Specification Front USB port Compatible with USB 2.0 Specification (Type A)
		Optional Local Ports	Internal RS-232C serial Parallel 1284-B Interface Card
		Optional Network Ports	Lexmark N4050e 802.11g Wireless Print Server (Print Only) External MarkNet™ N7020e Gigabit Ethernet Internal MarkNet™ N8120 Gigabit Ethernet Internal MarkNet™ N8130 Fiber Fast Ethernet Internal MarkNet™ N8150 802.11b/g/n Wireless
		Network Printing Methods	LPR/LPD Direct IP (Port 9100) Socket (Raw TCP/IP)

	CNC, ANATEL, SUBTEL, MTC, MOC, TK, TEC, SIRIM, ICASA, R&TTE ETSI ES 203 021,-2,-3
Maximum Monthly Duty Cycle: Up to	200000 pages per month
Recommended Monthly Page Volume	3000 - 20000 Pages
Specified Operating Environment	Temperature: 16 to 32°C (60 to 90° F) Humidity: 8 to 80% Relative Humidity Altitude: 0 - 3048 Meters (10,000 Feet)

Copyright © 2009 Lexmark International, UK. All rights reserved.
Registered in England & Wales No. 2567373 Registered Office: Westhorpe House, Westhorpe, Marlow, Buckinghamshire SL7 3RQ.

HTTP

	NDS Queue-based Printing NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services) Enhanced IP (Port 9400) FTP, TFTP IPP 1.1 (Internet Printing Protocol) ThinPrint .print integration
Network Protocol Support	TCP/IP IPv4 IPX/SPX AppleTalk™ LexLink (DLC) TCP/IP IPv6 TCP UDP
Network Management Protocols	HTTP HTTPs (SSL*/TLS) SNMPv3 WINS SLPv1 IGMP BOOTP, RARP APIPA (AutoIP) DHCP ICMP DNS SNMPv2c Bonjour DDNS mDNS ARP NTP Telnet Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.
Network Security	SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 158 scalable PostScript fonts 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts 84 scalable PCL fonts OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Printable Area	0.167 inches of the top, bottom, right and left edges (within)
Printable Area (metric)	4.2 mm of the top, bottom, right and left edges (within)
Printer Languages (Standard)	PCL 5e Emulation PCL 6 Emulation PPDS PostScript 3 Emulation xHTML PDF 1.6 Direct Image Microsoft XPS (XML Paper Specification)
Reduce / Enlarge Range	25 - 400 %
Scan Area, Maximum (mm)	216 x 355.6 mm
Modem Speed	33.6 Kbps
Packaged Size (mm - H x W x D)	1020 x 735 x 700 mm
Size (mm - H x W x D)	755 x 548 x 611 mm
Weight (kg)	45.4 kg
Weight (lb.)	100 lbs.
Noise Level, Idle	29 dBA
Noise Level, Operating	54 dBA
Copier Noise Level, Operating	55 dBA
Scanner Noise Level, Operating	56 dBA
Product Guarantee	1-Year Onsite Service, Next Business Day
Product Certifications	Energy Star, CE Class A, CB IEC 60950-1, IEC 60825-1, IEC 61000-3-2, IEC 61000-3-3, EN 55022 Class A, EN 55024, CISPR 22 Class A, IEC 60320, GS (TÜV), EN 60825-1, ACMA A-tick mark Class A, AS/NZS 60950-1, EK Mark, KCC MIC Mark, CCC Class A, UL AR, CS, TÜV Rh,

