



PRODUCTS | Multifunction Monochrome Laser



NEW!
LEXMARK X658DTFE
MFP

Benefits that no copier can copy!

[Get A Quote](#)
[FIND A DEALER](#)
[BUY ON LINE](#)
[Interactive tour](#)
[Support](#)
[Printer brochure](#)

OVERVIEW SUPPLIES AND OPTIONS TECH SPECS Q AND A

Print Technology	Laser, Monochrome
UNSPSC Code	43212110
Function	Colour Scanning Copying Faxing Network Scanning Printing .
Supplies: Functions only with replacement cartridges designed for use in Europe, the Middle East and Africa	
Print Speed (A4 mono): Up to	53 ppm
Print Speed (A4 mono) Duplex: Up to	36 spm
Print Speed (Letter mono): Up to	55 ppm
Print Speed (Letter mono) Duplex: Up to	37 spm
Time to First Page (Black) As fast as	9.5 seconds
Copy Speed (A4, Black): Up to	53 cpm
Time to First Copy (Black) As fast as	7.5 seconds
Simplex Scan Speed (A4 mono): Up to	55 sides per minute
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 600 x 600 dpi
Scanning Resolution	600 X 600 dpi (mono)
Processor	600 MHz
Memory, standard	256 MB
Memory network model, maximum	1280 MB
Expandable Memory Options	Yes
Apple Macintosh Operating Systems Supported	Apple Mac OS X Apple Mac OS 9.x
Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5 Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
Linux Operating Systems Supported	Linpus Linux Desktop 9.2, 9.3 Red Hat Enterprise Linux WS 3.0, 4.0, 5.0 SUSE Linux Enterprise Server 8.0, 9.0, 10.0 SUSE Linux Enterprise Desktop 10 openSUSE 10.2, 10.3, 11.0 Linspire Linux 6.0 Debian GNU/Linux 4.0

	CCC Class A, UL AR, CS, TÜV Rh, CNC, ANATEL, SUBTEL, MTC, MOC, TK, TEC, SIRIM, ICASA, R&TTE ETSI ES 203 021,-2,-3
Maximum Monthly Duty Cycle: Up to	275000 pages per month
Recommended Monthly Page Volume	5000 - 30000 Pages
Specified Operating Environment	Temperature: 16 to 32°C (60 to 90° F) Humidity: 8 to 80% Relative Humidity Altitude: 0 - 3048 Meters (10,000 Feet)

	HTTP
	NDS Queue-based Printing
	NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services)
	Enhanced IP (Port 9400)
	FTP, TFTP
	IPP 1.1 (Internet Printing Protocol)
	ThinPrint .print integration
Network Protocol Support	TCP/IP IPv4
	IPX/SPX
	AppleTalk™
	LexLink (DLC)
	TCP/IP IPv6
	TCP
	UDP
Network Management Protocols	HTTP
	HTTPs (SSL*/TLS)
	SNMPv3
	WINS
	SLPv1
	IGMP
	BOOTP, RARP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	SNMPv2c
	Bonjour
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.
Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
	IPSec
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	158 scalable PostScript fonts
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Printable Area	0.167 inches of the top, bottom, right and left edges (within)
Printable Area (metric)	4.2 mm of the top, bottom, right and left edges (within)
Printer Languages (Standard)	PCL 5e Emulation
	PCL 6 Emulation
	PPDS
	PostScript 3 Emulation
	xHTML
	PDF 1.6
	Direct Image
	Microsoft XPS (XML Paper Specification)
Reduce / Enlarge Range	25 - 400 %
Scan Area, Maximum (mm)	216 x 355.6 mm
Modem Speed	33.6 Kbps
Packaged Size (mm - H x W x D)	1445 x 1010 x 840 mm
Size (mm - H x W x D)	1246 x 548 x 596 mm
Weight (kg)	80.1 kg
Weight (lb.)	176.5 lbs.
Noise Level, Idle	28 dBA
Noise Level, Operating	55 dBA
Copier Noise Level, Operating	55 dBA
Scanner Noise Level, Operating	55 dBA
Product Guarantee	1-Year Onsite Service, Next Business Day
Product Certifications	Energy Star, CE Class A, CB IEC 60950-1, IEC 60825-1, IEC 61000-3-2, IEC 61000-3-3, EN 55022 Class A, EN 55024, CISPR 22 Class A, IEC 60320, GS (TÜV), EN 60825-1, ACMA A-tick mark Class A, AS/NZS 60950-1, EK Mark, KCC MIC Mark,

