



Sometimes you're ready
to spend it all.

Sometimes you don't have to.

Lexmark X850e

An affordable path
to workgroup efficiency!

A3

Up to 35 ppm

Low volume duty cycle

3100 sheets standard
input capacity

The perfect fit for your budget

Affordably priced, the X850e MFP offers a rich range of innovative features to help you work more easily and productively than ever before.

Now showing on the 'big screen'

The incredibly large, customisable touch-screen gives you fast access to a number of easy-to-use functions, including duplex colour scanning.

Faster and more robust

The X850e delivers 35 ppm print speeds, rapid time to first page, advanced finishing, and large standard input capacity of 3,100 sheets.

We make printing easy

LEXMARKTM

Lexmark X850e

Down with heavy costs. Up with productivity!

Ideal for small to mid-size businesses with wide-format mono needs, the Lexmark X850e takes care of all your printing, copying, scanning and faxing in just one compact device. Offering rapid 35 ppm print speeds and plenty of innovative features, it saves you time, money, floor space, and even electricity.

Touch the future

It doesn't take long to see why the X850e will be a welcome addition to your office. Its huge LCD touch-screen offers a visually attractive – and extremely practical – way to access all the features you need. Intuitive, adjustable and fully customisable, it's your gateway to greater business efficiency.

Scan and copy with ease

The large flatbed colour scanner is great for scanning and copying big reports. You can even preview scans on the LCD screen, or scan straight to a USB key. And if it's a big stack of 2-sided originals you need copied, no problem. Just place it into the 75-page Automatic Document Feeder, touch the screen and go!

Print Technology: Monochrome Laser

Function: Copying, Faxing, Network Scanning, Printing

Print Speed (A4, Black): Up to 35 ppm

Print Speed (A4, Black) Duplex

Up to 35 spm

Print Speed (Letter, Black): Up to 35 ppm

Print Speed (Letter, Black) Duplex

Up to 35 spm

Time to First Page (Black)

as fast as 6.8 seconds

Copy Speed (A4, Black): Up to 35 cpm

Time to First Copy (Black)

as fast as 10 seconds

Simplex Scan Speed (A4/Ltr, Black)

Up to 55 Sides per minute

Simplex Scan Speed (A4/Ltr, Color)

Up to 27.5 Sides per minute

Duplex Scan Speed (A4/Ltr, Black)

Up to 60 Sides per minute

Duplex Scan Speed (A4/Ltr, Color)

Up to 18 Sides per minute

Print Resolution, Black

1200 Image Quality, 1200 x 1200 dpi,

2400 Image Quality, 600 x 600 dpi

Scanning Resolution

600 X 600 dpi, 600 X 300 dpi (colour)

Processor: 625 MHz

Memory, Standard: 256 MB

Memory, Maximum: 768 MB

Expandable Memory Options: Yes

Apple Macintosh Operating Systems Supported

Apple Mac OS X, Apple Mac OS 9.x

Citrix MetaFrame

Linux Operating Systems Supported

Microsoft Windows Operating Systems Supported

Microsoft Windows 2000, (Professional/Server/Advanced Server), Microsoft Windows NT (4.00/4.00 Server), Microsoft Windows Me, Microsoft Windows XP (Home, Professional), Microsoft Windows Server 2003 (Standard, Enterprise), Microsoft Windows 98 2nd Edition, Microsoft Windows

XP Professional x64, Microsoft Windows Server 2003 (Standard, Enterprise) running Terminal Server, Microsoft Windows 2000 Server running Terminal Services, Microsoft Windows Server 2003 (Standard, Enterprise) x64 Edition, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Services

Novell Operating Systems Supported

UNIX Operating Systems Supported

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling Standard

500-Sheet Output Bin

Duplex Unit

Two 500-Sheet Trays, 100-Sheet Multipurpose Feeder, 2,000-Sheet Dual Input

Paper Handling Optional

2,000-Sheet High-capacity Feeder,

3,500-Sheet Finisher

Paper Input Capacity (Standard)

3100 pages 20 lb or 75 gsm bond

Paper Input Capacity (Maximum)

5100 pages 20 lb or 75 gsm bond

Paper Output Capacity (Standard)

500 pages 20 lb or 75 gsm bond

Paper Output Capacity (Maximum)

3800 pages 20 lb or 75 gsm bond

Copy/Fax/Scan (ADF) Paper Input Capacity : Up to 75 pages 20 lb or 75 gsm bond

Envelope Capacity: 10

Finishing Option? Yes

Number of Paper Inputs: 5

Number of Paper Inputs, Maximum: 6

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

A boost in performance

Maximise uptime and get your documents in your hands faster!

Combining rapid output speeds with a standard 3,100-sheet input capacity, and an optional finisher for stapling, stacking and hole-punch, the X850e delivers the uninterrupted performance you need to stay productive.

Solutions-ready

Take workflow efficiency to new levels. The X850e is equipped with Lexmark's new Embedded Solutions framework, offering you network-friendly, native support for Lexmark's wide range of enterprise solutions, such as Optra Forms, ImageQuick, DLE applications and many others.

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement

Standard Ports

Centronics IEEE 1284 Bidirectional Parallel, Ethernet 10/100BaseTX (RJ-45), One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel, Optional Local Ports, Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External 802.11g Wireless

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Network Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP

Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

TCP/IP Set of Application Services

Zero configuration, DDNS, mDNS, NTP:

Network Time Protocol, ping, finger, telnet, TFTP

Network Management Protocols

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, SLPV1, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS

Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area

0.157 inches of the top, bottom, right and left edges (within)

Printable Area (metric)

4 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.5

Reduce / Enlarge Range: 25 - 400 %

Scan Area, Maximum (mm): 297 x 432 mm

Modem Speed: 33.6 Kbps

Packaged Size (mm - H x W x D)

1380 x 890 x 850 mm

Size (mm - H x W x D)

1095 x 640 x 700 mm

Weight (kg): 105.7 kg

Weight (lbs): 233 lbs.

Noise Level, Idle: 32 dBA

Print Noise Level, Operating: 52 dBA

Copy Noise Level, Operating: 56 dBA

Scan Noise Level, Operating: 54 dBA

Product Warranty: One Year or 600,000 impressions - OnSite Repair

Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 320-1, ECMA-74, CE Class A, CB IEC 60950 1, IEC 61000-3-2 and -3-3, EN 55022, EN 55024, CISPIR 22 Class A, GS (TÜV)-EN 60950-1, SEMKO, UL AR, CS, TÜV Rh, N Mark, C-tick Class A, CCC Class A, RPC, PSB, MIC, EK - K60950

Duty Cycle: Up to 150,000 one-time maximum Impressions per month

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F)

Humidity: 8 to 80% Relative Humidity

Altitude: 0 - 3048 Meters (10,000 Feet)



Supplies

Ships with 30K* pages Return toner cartridge
Ships with 60K Photoconductor Kit
30K* pages High Yield toner cartridge (aftermarket).
48K pages Photoconductor Kit

- Printers and supplies are designed for use in Europe, Middle East and Africa only

* Average cartridge yield. Declared yield value in accordance with ISO/ IEC 19752.

Model available

- X850e



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.com

LEXMARK
TM