

Specification

400CX(N)-2

460CX(N)-2



		400CX(N)-2	460CX(N)-2
Display	Screen Size	40"	46"
	Brightness (Typical)	450 cd/m ²	450 cd/m ²
	Contrast Ratio (Typical)	4000:1	4000 : 1
	Resolution	1920x1080	1920x1080
	Response Time (Typical)	8ms (GTG)	8ms (GTG)
	Viewing Angle (Horizontal/Vertical)	178°/178°	178°/178°
	Color Support	16.7 M	16.7 M
Signal Input	Video Signal	Analog RGB, DVI -D, Composite, HDMI, D/A-TV	Analog RGB, DVI -D, Composite, HDMI, D/A-TV
	Sync. Signal	Separate H/V, Composite, SOG	Separate H/V, Composite, SOG
	Connector	D-SUB, RS232C, DVI, HDMI, CVBS, D-TV	D-SUB, RS232C, DVI, HDMI, CVBS, D-TV
Power	Power Consumption	290W	330W
	Stand By Power (DPMS)	2W (5W)	5W (Energy Saving ON)
	Type	Internal	Internal
Feature	Plug & Play	DDC 2B	DDC 2B
	USB Powered Hub Option	No	No
	Mac compatibility	Yes	Yes
	Multi Speaker	10Wx2Ch (Built-in)	10Wx2Ch (Built-in)
	Wall-Mount (mm)	Mounting Kit Available (Option)	Mounting Kit Available (Option)
	TCO	No	No
	Cabinet Color	Black Glossy	Black Glossy
	Accessory	Manuals, D-Sub Cable (Option), Power Cord, Remote Control, Batteries, Cleaning Cloth	Manuals, D-Sub Cable (Option), Power Cord, Remote Control, Batteries, Cleaning Cloth
	Special Feature	Magic Info, Lamp Error Detection, Matrix Video Wall(2x2, 3x3, 4x4, 1x5, 5x1, 5x5), Safety Lock, Temperature Sensor, Built in Fan, RS232C, Built-in Network (Option)	Magic Info, Lamp Error Detection, Matrix Video Wall(2x2, 3x3, 4x4, 1x5, 5x1, 5x5), Safety Lock, Temperature Sensor, Built in Fan, RS232C, Built-in Network (Option)
Dimension	Product Dimension (With Stand, WxHxD, mm)	941 x 641.5 x 311	1102 x 719 x 311
	Product Dimension (Without Stand, WxHxD, mm)	971 x 582 x 119	1102 x 658 x 125.5
	Shipment Dimension (WxHxD, mm)	1085 x 703 x 310	1220 x 780 x 310
Weight	Product Weight (Kg)	21	28.4
	Shipment Weight (Kg)	26.1	34.4
Stand	Type	Foot Stand (Optional)	Foot Stand (Optional)
	Function	No	No