

Specification

400DX(N)-2

460DX(N)-2



| | | 400DX(N)-2 | 460DX(N)-2 |
|--------------|--|---|---|
| Display | Screen Size | 40" | 46" |
| | Brightness (Typical) | 700 cd/m ² | 700 cd/m ² |
| | Contrast Ratio (Typical) | 3000 : 1 (DC 30000 : 1) | 4000 : 1 (DC 30000 : 1) |
| | Resolution | 1920x1080 | 1920x1080 |
| | Response Time (Typical) | 8ms | 8ms |
| | Viewing Angle (Horizontal/Vertical) | 178°/178° | 178°/178° |
| | Color Support | 16.7 M | 16.7 M |
| Signal Input | Video Signal | Analog RGB, DVI -D, HDMI, CVBS | Analog RGB, DVI -D, HDMI, CVBS |
| | Sync. Signal | Separate H/V,SOG | Separate H/V,SOG |
| | Connector | D-SUB, DVI-D, CVBS, HDMI (BNC, Component) | D-SUB, DVI-D, CVBS, HDMI |
| Power | Power Consumption | 300W | 350W |
| | Stand By Power (DPMS) | 1W (5W) | <5W |
| | Type | Internal | Internal |
| Feature | Plug & Play | DDC 2B | DDC 2B |
| | USB Powered Hub Option | No | No |
| | Mac compatibility | Yes | Yes |
| | Multi Speaker | 10Wx2Ch (Built-in) | 10Wx2Ch (Built-in) |
| | Wall-Mount (mm) | Mounting Kit Available (Option) | Mounting Kit Available (Option) |
| | TCO | No | No |
| | Cabinet Color | Black | Black |
| | Accessory | Quick Setup Guide, Warranty Card, User's Guide, Power Cord, Remote Control, Batteries | Quick Setup Guide, Warranty Card, User's Guide, Power Cord, Remote Control, Batteries |
| | Special Feature | Maginfo, Anti-image Retention, Video Wall upto 5x5, Safety Lock, RS-232C | Maginfo, Anti-image Retention, Video Wall upto 5x5, Safety Lock, RS-232C |
| Dimension | Product Dimension (With Stand, WxHxD, mm) | 932 x 604 x 311 | 1068 x 681 x 311 |
| | Product Dimension (Without Stand, WxHxD, mm) | 932 x 548 x 130 | 1068 x 624 x 130 |
| | Shipment Dimension (WxHxD, mm) | 1043 x 667 x 311 | 1190 x 763 x 305 |
| Weight | Product Weight (Kg) | 23 | 29 |
| | Shipment Weight (Kg) | 27.5 | 33 |
| Stand | Type | Semi Stand (Option) | Semi Stand (Option) |
| | Function | No | No |