

# Specification

400MX(N)-2

460MX(N)-2



		400MX(N)-2	460MX(N)-2
Display	Screen Size	40"	46"
	Brightness (Typical)	450 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>
	Contrast Ratio (Typical)	4000:1	4000 : 1
	Resolution	1920x1080	1920x1080
	Response Time (Typical)	8ms (GTG)	8ms (GTG)
	Viewing Angle (Horizontal/Vertical)	178°/178°	178°/178°
	Color Support	16.7 M	16.7 M
Signal Input	Video Signal	Analog RGB, DVI-D, CVBS, HDMI	Analog RGB, DVI-D, CVBS, HDMI
	Sync. Signal	Separate H/V, Composite, SOG	Separate H/V, Composite, SOG
	Connector	D-SUB, DVI-D, HDMI, CVBS, RS232C	D-SUB, DVI-D, HDMI, CVBS, RS232C
Power	Power Consumption	290W	330W
	Stand By Power (DPMS)	1W (5W)	1W (5W)
	Type	Internal	Internal
Feature	Plug & Play	DDC 2B	DDC 2B
	USB Powered Hub Option	No	No
	Mac compatibility	Yes	Yes
	Multi Speaker	10Wx2Ch (Built-in)	10Wx2Ch (Built-in)
	Wall-Mount (mm)	Mounting Kit Available (Option)	Mounting Kit Available (Option)
	TCO	No	No
	Cabinet Color	Black	Silver
	Accessory	User Manual, Warranty Card, Application CD, Power Cable, Remote Controller	User Manual, Warranty Card, Application CD, Power Cable, Remote Controller
	Special Feature	Lamp Error Detection, Matrix Video Wall (2x2, 3x3, 4x4, 1x5, 5x1, 5x5), Safety Lock, Temperature Sensor, Built-in Fan, RS232C, Built-in Network (Option)	Lamp Error Detection, Matrix Video Wall (2x2, 3x3, 4x4, 1x5, 5x1, 5x5), Safety Lock, Temperature Sensor, Built-in Fan, RS232C, Built-in Network (Option)
	Dimension	Product Dimension (With Stand, WxHxD, mm)	971 x 643 x 311
Product Dimension (Without Stand, WxHxD, mm)		971 x 582 x 118.5	1102 x 658 x 125.5
Shipment Dimension (WxHxD, mm)		1085 x 703 x 310	1220 x 780 x 310
Weight	Product Weight (Kg)	20.4	28.4
	Shipment Weight (Kg)	23.9	34.4
Stand	Type	Foot Stand (Optional)	Foot Stand (Optional)
	Function	No	No