

Specification

400UX(N)-2

460UX(N)-2

40"

46"

		400UX(N)-2	460UX(N)-2
Display	Screen Size	40"	46"
	Brightness (Typical)	700 cd/m ²	700 cd/m ²
	Contrast Ratio (Typical)	3000 : 1 (DC:30000 : 1)	4000 : 1 (DC:30000 : 1)
	Resolution	1920x1080	1920x1080
	Response Time (Typical)	8ms	8ms
	Viewing Angle (Horizontal/Vertical)	178°/178°	178°/178°
	Color Support	16.7 M	16.7 M
Signal Input	Video Signal	Analog RGB, DVI -D, HDMI, CVBS	Analog RGB, DVI -D, HDMI, CVBS
	Sync. Signal	Separate H/V, SOG	Separate H/V, Composite, SOG
	Connector	D-SUB, DVI-D, CVBS, HDMI	D-SUB, DVI-D, CVBS, HDMI
Power	Power Consumption	300W	350W
	Stand By Power (DPMS)	2W (5W)	2W (5W)
	Type	Internal	Internal
Feature	Plug & Play	DDC 2B	DDC 2B
	USB Powered Hub Option	No	No
	Mac compatibility	Yes	Yes
	Multi Speaker	10Wx2Ch (Built-in)	10Wx2Ch (Built-in)
	Wall-Mount (mm)	Mounting Kit Available (Option)	Mounting Kit Available (Option)
	TCO	No	No
	Cabinet Color	Black	Black
	Accessory	Quick Setup Guide, Warranty Card, User's Guide, Power Cord, Remote Control, Batteries	Quick Setup Guide, Warranty Card, User's Guide, Power Cord, Remote Control, Batteries
	Special Feature	MagicInfo, Anti-image Retention, Video Wall upto 5X5, Safety Lock, PIP, RS-232C	MagicInfo, Anti-image Retention, Video Wall upto 5X5, Safety Lock, PIP, RS-232C
	Dimension	Product Dimension (With Stand, WxHxD, mm)	914 x 585 x 311
Product Dimension (Without Stand, WxHxD, mm)		914 x 526.2 x 121.5	1050 x 603 x 119.5
Shipment Dimension (WxHxD, mm)		1015 x 652 x 300	1155 x 733 x 325
Weight	Product Weight (Kg)	22.2	27.7
	Shipment Weight (Kg)	26	32.5
Stand	Type	No	No
	Function	No	No